

RAISING THE **BAR**

OUR MARATHON HOSE HOLDS STRONG



*Industry leading
pressure ratings*



**Muncie[®]
Power
Products**

INDUSTRY LEADING PRESSURE RATINGS






available in 1/4" (6,525 PSI MAX Working Pressure) through 1" (3,625 PSI MAX Working Pressure)

NO-SKIVE HOSE

IMPULSE TESTED
(up to 1,000,000 cycles)

**UTILIZES INTERPUMP
ONE-PIECE G FITTINGS**

4:1 SAFETY RATED

Part Number							
	ID	Size	OD	MAX WP		MIN BR	Weight (approx.)
	in.			in.	BAR		
BHEYM2K-04	1/4	04	0.52	450	6,525	1.969	0.192
BHEYM2K-05	5/16	05	0.58	420	6,090	2.362	0.222
BHEYM2K-06	3/8	06	0.67	385	5,583	2.756	0.284
BHEYM2K-08	1/2	08	0.82	350	5,075	3.150	0.349
BHEYM2K-10	5/8	10	0.93	350	5,075	3.543	0.447
BHEYM2K-12	3/4	12	1.09	280	4,060	4.725	0.531
BHEYM2K-16	1	16	1.42	250	3,625	5.512	0.934

Hose construction:

Internal hose: Synthetic rubber, singular extrusion, uniform thickness

Reinforcement: 2 high tensile steel wire braids

External covering: Smooth anti-abrasive synthetic rubber, resistant to oils, fuels, and atmospheric conditions

Recommended fluid:

Petroleum based hydraulic fluids, glycol-water based fluids and lubricants

Operating temperature range:

-40° F to +248° F (-40° C to +120° C)
Intermittent +275° F (+135° C)

ih INTERPUMP ■■■ **MARATHON** >>> **EXCEEDS EN 857/ISO 11237 - 2SC DN 12 I.D. 1/2" - W.P. 350 BAR/5075 PSI**

Built to INTERconnect.



MEMBERS OF THE INTERPUMP GROUP

201 EAST JACKSON STREET • MUNCIE, INDIANA 47305 • 844-745-6335 • MUNCIEPOWER.COM/HOSE